

ESSENCE

Wide-plank Xcora® Flooring



FINE BAMBOO FLOORING, PANELS & WORKTOPS

Teragren's best-selling Xcora® Strand bamboo floors get the all-star treatment in our Essence Collection. Ultra-wide planks, multiple hand-applied coats of beautiful color, textures including hand-scraping, wirebrushing, natural saw marks – all on our strand bamboo wear layer that averages 160% harder than red oak. When it comes to dimension, depth, and durability, the Essence collection is second to none.



FEATURES + BENEFITS

PERFORMANCE

- TrueMark® Glaze Tek- 4 coats of hand applied base & accent color, with 12 coats of finish
- Premium Xcora® strand bamboo – 160% harder than red oak
- Optimum 5.5 Moso Bamboo: Harvested at maturity for peak density, creating a harder and more stable product for lasting beauty and performance

VALUE

- Lifetime structural warranty; 10-year heavy-use commercial/25-year residential finish warranties

ECOSMART

- Certified USDA BioPreferred – 99% biobased content
- 100% FSC®- Certified material available upon request*
- Standard FSC® Certified Core – Eucalyptus & Poplar
- Wear Layer is made of MR6 rapidly Renewable Materials

INDOOR AIR QUALITY

- Floorscore certified for superior indoor air quality.
- Qualifies for Collaborative for High Performance Schools 2009 Criteria EQ2.2.3 – Low Emitting Materials

PRODUCT DETAILS

Nominal Dimensions :	72.83" x 7.48" x .55" (1850mm x 190mm x 14mm)
Construction:	Engineered Xcora® Strand Bamboo
Wear Layer:	3mm
Milling:	4 Side Micro bevel
Profile:	Tongue and Groove
Accessories:	Full line of coordinating 14mm accessories
Color Variation:	Moderate

INSTALLATION + CARE

Installation Environment:	Nail, Glue installation into environments having 35-55% RH.
Nail & Staple Installation:	On or Above grade. Use vapor retarder over wood subfloor.
Glue Installation:	On or Above grade. Use a vapor barrier over cement subfloor OR vapor retarder over wood subfloor.
Recommended Adhesive:	Premium Bamboo Flooring Adhesive
Nailing Guidelines:	18 or 20 gauge cleat x 1.5"
Acclimation:	Minimum of 48 hours on-site in box
Maintenance:	TrueClean Floor Cleaner




ESSENCE Open Range

LEED® CREDITS


- IEQ 4.3 Low Emitting Materials
- Certified Wood: MR7 – *available upon request




Grasslands




Meadows




Open Range



Prairie



Savanna



Tundra