

NEOTERA

Wide-plank Xcora® Flooring



FINE BAMBOO FLOORING, PANELS & WORKTOPS

The Neotera Collection showcases the “New Teragren” in a gorgeous range of 5 clean, contemporary colors with just the right amount of texture and natural, open grain. Featuring our best-selling Xcora® Strand bamboo wear layer over a eucalyptus/poplar core, this collection boasts all the durability of strand bamboo with all the stability and flexibility of an engineered construction.



FEATURES+ BENEFITS

PERFORMANCE

- TrueMark® Glaze Tek- 4 coats of hand applied base & accent color, with 12 coats of finish
- Premium Xcora® strand bamboo – 160% harder than red oak
- Optimum 5.5 Moso Bamboo: Harvested at maturity for peak density, creating a harder and more stable product for lasting beauty and performance

VALUE

- Lifetime structural warranty; 10-year heavy-use commercial/25-year residential finish warranties

ECOSMART

- Certified USDA BioPreferred – 99% biobased content
- 100% FSC®- Certified material available upon request*
- Standard FSC® Certified Core – Eucalyptus & Poplar
- Wear Layer is made of MR6 rapidly Renewable Materials

INDOOR AIR QUALITY


- Floorscore certified for superior indoor air quality.
- Qualifies for Collaborative for High Performance Schools 2009 Criteria EQ2.2.3 – Low Emitting Materials

PRODUCT DETAILS

Nominal Dimensions :	72.83" x 5.12" x .47" (1850mm x 130mm x 12mm)
Construction:	Engineered Xcora® Strand Bamboo
Wear Layer:	2mm
Milling:	4 Side Micro bevel
Profile:	Tongue and Groove
Accessories:	Full line of coordinating 12mm accessories
Color Variation:	Moderate

INSTALLATION + CARE


Installation Environment:	Nail, Glue installation into environments having 35-55% RH.
Nail & Staple Installation:	On or Above grade. Use vapor retarder over wood subfloor.
Glue Installation:	On or Above grade. Use a vapor barrier over cement subfloor OR vapor retarder over wood subfloor.
Recommended Adhesive:	Premium Bamboo Flooring Adhesive
Nailing Guidelines:	18 or 20 gauge cleat x 1.5"
Acclimation:	Minimum of 48 hours on-site in box
Maintenance:	TrueClean Floor Cleaner



NEOTERA Pollock

LEED® CREDITS


- IEQ 4.3 Low Emitting Materials
- Certified Wood: MR7 – *available upon request



Rothko




Pollock



Warhol



Kruger



Sherman